



## RMR through your Central Station

LifeSentry Kit: Model #37911



Base Station



Pendant

Optional Accessory:  
*Emergency Wall Communicator*  
Model #37920



**Water Resistant** The pendant allows one to summon help even if they are in the bath or shower, where serious accidents can happen. Meets the IPX-5 water spray test.

**Voice Prompted System** Provides announcements during set-up, programming, testing, battery test and full system check.

**Pendant Battery** A lithium-ion battery provides over 4 hours of talk time on a full charge, and up to 4 months in stand-by. Two such rechargeable batteries are included. One charges in the base station charger, while the other is in the pendant. Simply swap the batteries around every few months. Press the battery test button on the back of the pendant for a second to hear an audible announcement - "battery is OK", "battery is low", or "replace battery now". No more guessing about battery status.

**System has Standby Emergency Battery Power** 4 NiMh rechargeable batteries continually charge in the base station to provide up to 24 hours of standby power in the event of a power failure.

**Central Station Compatible** Uses industry standard "Contact ID" transmission format.

**Fully Supervised** The pendant checks in with the base station every 13 hours to confirm its battery status and that it is functioning. In the event of, power loss, a very low battery or loss of RF signal - the base will relay the information to the central station.

**Line-Seizure** Built-in relay allows system to seize the line during the emergency.

**Multiple Devices** Up to a total of 4 pendants & *Emergency Wall Communicators* can be associated to a single base station. Great for senior group homes.

**Pendant can be carried in 3 convenient ways.** Included with each system is a **Lanyard**, a **Wrist/Wheel-chair Strap** holder and a **Belt Clip**.

**Approved in all 50 states and Canada.** FCC & DOC certified. Factory is ISO-9001 approved. DECT Technology - 1.9 Ghz.

**Shipping weight:** 1.9 lbs each (3 per inner carton - 12 per master carton)  
**Patented Technology.**

LogicMark, LLC



1.888.912.6121  
250.428.9696

[www.csystemssecurity.com](http://www.csystemssecurity.com)